



FEATURES

Dimensions

External dimensions	682 x 602 x 1646 [mm] (W x D x H)
Dimensions with removable wheels	H = 1714 [mm]
Interior dimensions	3 compartments of 480 x 400 x 400 [mm] (W x D x H)
Interior fittings	up to 5 shelving layers per compartment (adjustable)
Interior lightning	LED blue
Door hinge	Left side
Net volume	230 liters
Weight	180 kg

Material

Material interior body	Plastic PMMA white
Material outer casing	Galvanized sheet steel white coated
Door	Polycarbonate 7mm

RFID operation

Carrier frequency	125 kHz
Technology	Passive RFID
Tag Type	Parcel Label, Parcel Inlay
	Swing Tag
Chip type	SPC R8
Memory	Read Only 126 bits
Data durability	10 years
Scan speed	15 items/sec

Access control

Lock	Electronic Rotary Latch
Biometrical	Finger print reader
RFID	Smart card ISO 15693 reader
Mechanical	Manual emergency release

Alarms

Door management	Open/close detector
Shocks	Accelerometer
Intrusion	Volumetric IR sensor
Cable disconnection	USB signal detector

Communication

Local network	USB
IP Network	RJ47- Ethernet /PC board IEM, Z510

Software

Software Development Kit	Windows .NET based
Business Application SmartTracker™	Local data base (standalone mode)
	Central data base (network mode)

Environmental

Power supply	100-230V AC, 50-60Hz
	Power on switch
Power consumption	200 W max
Operating temperature	10 to 40°C or 50° to 104°F (indoor use)
EMC	ETSI/CE